

# PL Series

## PL1500/PL1500-A

### Applications

- Live club performance
- Multi-functional auditorium
- Fill-in system for main PA
- MI market system

### Features

- Strong plastic enclosure
- Molded-in 120° X60° horn
- High power output
- Flexible mounting options

### 15" Two-Way Full Range Plastic Speaker

The PL1500 is a versatile, compact, two-way passive system. It features a long-excursion 15"(380mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn



### Applications

- Live club performance
- Multi-functional auditorium
- Fill-in system for main PA
- MI market system

### Features

- Active speaker system
- Strong plastic enclosure
- Molded-in 120° X60° horn
- High power output
- Flexible mounting options

### 15" Two-Way Full Range Active Plastic Speaker

The PL1500-A is a versatile, compact, two-way active passive system. It features a long-excursion 15"(380mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn

### Specifications

	PL1500	PL1500-A
Frequency Response	60Hz-20kHz(±3dB)	60Hz-20kHz(±3dB)
Low Frequency Limit	48Hz(-10dB)	48Hz(-10dB)
Drivers	1X15"(380mm)/2.5"(65mm) voice coil LF drivers 1X1"(25mm) exit compression driver	1X15"(380mm)/2"(65mm) voice coil LF drivers 1X1"(25mm) exit compression driver
Power Rated(RMS)	350W, 1400W peak	400W, 1000W peak
Recommended Amp	400-600W	
Sensitivity(1w/1m)	97dB	97dB
SPL	120dB continuous, 126 dB peak	121dB continuous, 127 dB peak
Nominal Impedance	8 Ω	8 Ω
Dispersion(HxV)	120° X60°	120° X60°
Crossover	2kHz	2kHz
Connector	2XNL4/1+1-	2XNL4/1+1-
Fittings	2X M8 mounting points	2X M8 mounting points
Pole Mount	1X top pole mount	1X top pole mount
Dimensions	485mmX745mmX415mm	485mmX745mmX415mm
Weight	17.6kg	25.2kg

## PX1200/PX1500

# PX Series

### Applications

- Live club performance
- Multi-functional auditorium
- Fill-in system for main PA
- MI market system

### Features

- Strong plastic enclosure
- Molded-in 120° X60° horn
- High power output
- Flexible mounting options

### 12" Two-Way Full Range Plastic Speaker

The PX1200 is a versatile, compact, two-way system. It features a long-throw 12"(300mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn



### Applications

- Live club performance
- Multi-functional auditorium
- Fill-in system for main PA
- MI market system

### Features

- Strong plastic enclosure
- Molded-in 120° X60° horn
- High power output
- Flexible mounting options

### 15" Two-Way Full Range Plastic Speaker

The PX1500 is a versatile, compact, two-way passive system. It features a long-excursion 15"(380mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn

### Specifications

	PX1200	PX1500
Frequency Response	60Hz-20kHz(±3dB)	60Hz-20kHz(±3dB)
Low Frequency Limit	48Hz(-10dB)	48Hz(-10dB)
Drivers	1X12"(300mm)/3"(75mm) voice coil LF drivers 1X1"(25mm) exit compression driver	1X15"(380mm)/2.5"(65mm) voice coil LF drivers 1X1"(25mm) exit compression driver
Power Rated(RMS)	250W, 1400W peak	350W, 1400W peak
Recommended Amp	300-600W	400-600W
Sensitivity(1w/1m)	93dB	97dB
SPL	120dB continuous, 126 dB peak	120dB continuous, 126 dB peak
Nominal Impedance	8 Ω	8 Ω
Dispersion(HxV)	120° X60°	120° X60°
Crossover	2kHz passive	2kHz passive
Protective Grille	Black perforated steel	Black perforated steel
Connector	2X Neutrik Speakon NL4	2X Neutrik Speakon NL4
Fittings	2X M8 threaded inserts	2X M8 threaded inserts
Pole Mount	1X top hat fitting	1X top hat fitting
Dimensions	428mmX600mmX320mm	465mmX690mmX400mm
Weight	18kg	24kg