

PS series

PS1000/PS1000-A

Applications

- Live club performance
- Fill-in system for mainPA
- MI market system

Features

- Strong plastic enclosure
- Molded-in 120° X60° constant directivity horn
- High power output
- Flexible mounting options

10" Two-Way Full Range Plastic Speaker

The PS1000 is a versatile, ultra-compact, two-way passive system. It features a long-throw 10"(250mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn



Applications

- Live club performance
- Fill-in system for mainPA
- MI market system

Features

- Active speaker system
- Strong plastic enclosure
- Molded-in 120° X60° constant directivity horn
- High power output
- Flexible mounting options

10" Two-Way Full Range Active Plastic Speaker

The PS1000-A is a versatile, ultra-compact, two-way active passive system. It features a long-throw 10"(250mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn

Specifications

	PS1000	PS1000-A
Frequency Response	68Hz-20kHz(±3dB)	68Hz-20kHz(±3dB)
Low Frequency Limit	55Hz(-10dB)	55Hz(-10dB)
Drivers	1X10"(250mm)/2"(50mm) voice coil LF drivers 1X1"(25mm) exit compression driver	1X10"(250mm)/2"(50mm) voice coil LF drivers 1X1"(25mm) exit compression driver
Power Rated(RMS)	200W, 800W peak	250W, 1000W peak
Recommended Amp	300-600W	—
Sensitivity(1w/1m)	96dB	95dB
SPL	118dB continuous, 124 dB peak	117dB continuous, 123 dB peak
Nominal Impedance	8Ω	8Ω
Dispersion(HxV)	120° X60°	120° X60°
Crossover	2.5kHz	2.5kHz
Connector	2XNL4/1+1-	2XNL4/1+1-
Pole Mount	1XTop pole mount	1XTop pole mount
Dimensions	347mmX534mmX314mm	347mmX534mmX314mm
Weight	10.1kg	13.6kg

PL Series

PL1200/PL1200-A

Applications

- Live club performance
- Multi-functional auditorium
- Fill-in system for mainPA
- MI market system

Features

- Strong plastic enclosure
- Molded-in 120° X60° horn
- High power output
- Flexible mounting options

12" Two-Way Full Range Plastic Speaker

The PL1200 is a versatile, compact, two-way system. It features a long-throw 12"(300mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn



Applications

- Live club performance
- Multi-functional auditorium
- Fill-in system for mainPA
- MI market system

Features

- Active speaker system
- Strong plastic enclosure
- Molded-in 120° X60° horn
- High power output
- Flexible mounting options

12" Two-Way Full Range Active Plastic Speaker

The PL1200-A is a versatile, compact, two-way active system. It features a long-throw 12"(300mm) low frequency driver and a 1"(25mm) exit compression driver mounted on a constant directivity 120° X60° horn

Specifications

	PL1200	PL1200-A
Frequency Response	60Hz-20kHz(±3dB)	60Hz-20kHz(±3dB)
Low Frequency Limit	48Hz(-10dB)	48Hz(-10dB)
Drivers	1X12"(300mm)/3"(75mm) voice coil LF drivers 1X1"(25mm) exit compression driver	1X12"(300mm)/2.5"(65mm) voice coil LF drivers 1X1"(25mm) exit compression driver
Power Rated(RMS)	250W, 1000W peak	300W, 1200W peak
Sensitivity(1w/1m)	93dB	93dB
SPL	120dB continuous, 126 dB peak	120dB continuous, 126 dB peak
Nominal Impedance	8Ω	8Ω
Dispersion(HxV)	120° X60°	120° X60°
Crossover	2kHz	2kHz
Connector	2XNL4/1+1-	2XNL4/1+1-
Fittings	2XM8 Mounting points	2XM8 Mounting points
Pole Mount	1XTop pole mount	1XTop pole mount
Dimensions	400mmX615mmX340mm	400mmX615mmX340mm
Weight	16kg	20kg